


QuickTARGET Unlimited

Preliminary User's Manual



Exterior Ballistics Program

Using a 3-DOF Model

Warning/Disclaimer:

SINCE WE HAVE NO CONTROL OVER EQUIPMENT, COMPONENTS, DATA HANDLOADING TECHNIQUES OR ANY OTHER VARIABLES THAT MIGHT BE USED WITH THIS PROGRAM, NO RESPONSIBILITY IS IMPLIED OR ASSUMED FOR ANY RESULTS OBTAINED THROUGH SUCH USE.

WE SPECIFICALLY DISCLAIM ANY AND ALL LIABILITY, INCLUDING CONSEQUENTIAL DAMAGES OF ANY KIND WHATSOEVER, WHETHER OR NOT ANY SUCH DAMAGES ARE DUE TO USER'S NEGLIGENCE OR BASED UPON STRICT PRODUCT LIABILITY OR PRINCIPLES OF INDEMNITY OR CONTRIBUTION. THE INDIVIDUAL MUST ASSUME THE ENTIRE RISK OF USING THIS PROGRAM AND ANY RESULTING DATA.

In this documentation, the naming of other manufacturer's products occurs exclusively for information purposes. This represents no trademark misuse.

Refer to *QuickLOAD* User's guide for complete information on the software license agreement, applicable laws and regulations.

No part of this document may be copied, reprinted, reproduced or transmitted in any forms or by any means, electronic, mechanical or optical, for any purpose, without the author's express written permission.

Due to continuous program updates, information in this document is subject to change without notice and can differ from the version of the program supplied. Be advised that the current version of *QuickTARGETUnlimited* may contain useful functions that this manual does not reflect.

All *QuickTARGETUnlimited* functions are available through standard menu item selections (review the *QuickLOAD Unlimited* manual for information on choosing menu items).

© Copyright 2002 - 2010, Hartmut G. Broemel, D-64832 Babenhausen / Germany, January 2010. Worldwide all rights reserved.

Program Installation

QuickTARGET Unlimited program must be installed together with *QuickLOAD* to and run from a hard disk drive. It is automatically installed during installation of *QuickLOAD* and cannot be installed separately.

For Program installation instructions, refer to the appropriate section of *QuickLOAD Manual*.

Contents

Warning/Disclaimer:	2
Program Installation	3
Foreword	5
Starting QuickTARGET unlimited	6
Important keyboard commands	6
Coordinate System of <i>QuickTARGET Unlimited</i>	7
Main Window	8
Main Menu Bar	9
Menu File	9
Print Selection Window	10
Menu Auxiliary Calculations	11
Menu Options	14
User's Settings of Units	17
Wind-Rose Window	18
Gun Sight-In Conditions Window	19
Trajectory Table Conditions Window	24
Displaying Results	27
Menu Copy to...	27
Menu Output Options	27
Menu Show...	28
Trajectory Table	29
Changing Graph's Appearance	30
Graph Window	30
Examples of Different Graphs in the Order of Menu	33
Drag Table Graph	33
Drop in Ground-Fixed-Frame	34
Path in Ground-Fixed-Frame	35
Path versus Line Of Sight	35
Velocity Graph	36
Energy Graph	36
Time of Flight	37
MOA Elevation Correction to Zero-In	37
MOA Azimuth Correction to Zero-In	38
Top View: Azimuth Deflection	38
Different Examples of Graphs	39
APPENDIX	42
Drag Table Files	42
Wind Profile Files	43
Bibliography	45
List of Illustrations	46

Foreword

QuickTARGET Unlimited is linked to *QuickLOAD*, our powerful Interior Ballistics Predictor Program. This version provides accurate and complete solutions to many "real-world" external ballistic questions.

At this time of writing, the program is still in the beta-phase and is added together with *QuickLOAD* and *QuickTARGET* to the CD. The addition "*unlimited*" has been used because the program has no restrictions like maximum ranges. It represents a Point-Mass Model or 3-Degrees-of-Freedom approach to the solution of exterior ballistics equations of motion.

Maybe a future version will expand this program to 4-DOF (**D**egrees-**O**f-**F**reedom) capabilities. This depends on finding a practical way to enable the user to make an estimate of all necessary coefficients needed for such calculations.

The program offers various drag tables together with the ability to use projectile specific drag tables read from external files without the need for Ballistic Coefficients.

It uses the same bullet files as *QuickLOAD* and *QuickTARGET*, but due to extensions, it is practical to edit bullet files under *QuickTARGET Unlimited*, otherwise some data entered by *QT-Unlimited* may be lost in bullet file.


The program provides more exact trajectory prediction at long ranges and is not restricted to very flat trajectories. One should know that programs maximum predicted horizontal ranges for spinning bullets are slightly too long, because a yawing bullet creates somewhat more drag and the maximum range will be slightly shorter. While the maximum vertical range calculation of the trajectory to vertex is very exact, the return from vertex to ground level is not, because of unknown drag of a bullet that returns base forward.

A 3-DOF model and even a 4-DOF model are not able to calculate precisely trajectories in the so-called upper group of angles for spinning projectiles (above 50 degrees angle of departure). Such calculations have to be done by solving 6-DOF equations of motion, which represent also only a semiempirical approach to the solution of exterior ballistics. However, the indeterminability of many initial conditions and aerodynamic coefficients, which are required as input is far beyond normal user's capabilities. Even if aerodynamic coefficients are available, there are more uncertainties, especially at barrel exit, that would affect trajectory prediction. Complete and accurate solutions to exterior ballistics projectile motion involves the solution of equations of fluid flow on the projectile, this is beyond the capabilities of available computers.

The user should be aware that the program distinguishes between *Sight-IN* conditions and *Trajectory table* conditions. For the beginner both conditions should be set to equal data, otherwise he will wonder about the results and cannot interpret them correctly.


Starting QuickTARGET unlimited

Double-click on program icon:



QuickTARGET Unlimited

After a few seconds of load and check time a text window with useful hints and warnings appears. Please read this text carefully. When you understand what it says, select the appropriate button, according to your decision.



Picture 1: Start and Disclaimer window

The license agreement and important advisories, which you must necessarily read, are found on the first pages of the *QuickLOAD* manual. For additional timely and important information, please review the *readme.txt* file on CD.

If the program does not start or aborts without providing an error notification, the program code could be corrupted (perhaps by a virus). The program tests for such corruption and usually provides a Checksum Failure error message. In either case, uninstall program and try to reinstall it from the installation disk. Error warnings during file loading (*QLOADFW.BUL*, *QLOADFW.INI* or *QTF.set*) indicate that the reported file is corrupt or does not exist in the program directory.


Important keyboard commands

To activate **main menu line**, press keyboard combination < ALT > + < PgUp >.

To activate and jump past **opened windows**, press keyboard combination < Ctrl > + < Tab >.


To select or bypass input fields, press < Tab >. "Arrow" (cursor control) keys also select **input fields**. To activate **drop-down fields**, press keyboard combination < Alt > + < ↓ > (e.g. Projectile). **Program exit** is initiated by pressing < Alt > + < F4 >.

Coordinate System of QuickTARGET Unlimited



Picture 2: Ground-Fixed Frame of Coordinates


The x-y plane lies in the direction of firing. Between muzzle velocity vector v_0 and x-z plane spans the angle of departure Φ_0 . The angle of impact into x-z plane is Φ . Forces on projectile are Drag Force vector F , velocity vector v and Gravity vector g .



Picture 3: Gunsite Angle

Gunsite angle is defined by target position. Target center is assumed to be in the x-y plane. The line between target center and muzzle forms an angle to x-axis : the Angle of Gunsite. The x-z plane is horizontal to Earth's surface; the origin of x-z plane is located at gunsite altitude above sea level.

When the user accepts the agreement window, this window opens:



Picture 4: Main Window

This is where the user inserts all basic gun and load data.

This data entry window allows specification of all data that is essential to trajectory table calculations. The user can enter useful values into all fields. The button **Receive data from QuickLOAD** retrieves values entered in *QuickLOAD* (when that program is running, or the latest data *QuickLOAD* has produced.).

NOTE: Input character of decimal point is the keyboard "period" character, even when user presses a comma it is converted. This is independent of Windows Operating System "Locale" settings.

Some fields for numerical inputs verify lower and upper limits for data entry. Violation of these limits produces a light red background color for "too high" or light blue color for "too low" value in the entry field. However, since this program cannot check every keystroke for simply incorrect entries, it is possible to run calculations with spurious input values.


Main Menu Bar



Picture 5: Main Menu Bar

So far the graph Window is not in foreground, the main menu bar shows the above configuration. **Main menu line** contains sub-menus: **File**, **Auxiliary Calculations** and **Options**.

Menu File




Picture 6: File Menu

Clicking to the word **F**ile or pressing keys, ALT-F invokes the File menu. It contains the following menu items:

- ❖ *Calculate Ballistics:*
 - Starts calculation, same effect as command button Calculate in the icon bar. After finishing calculation, a trajectory table or a graph window is displayed. After opening of the output window, the menu changes to enable the user to set up graph settings.
- ❖ *Save trajectory data*
 - So far, valid data exists; the file save window is opened. User may specify an appropriate file name and save the settings and data of the Sight-In- and in the Table Setup Window.
- ❖ *Load trajectory data*
 - Opens the open file dialogue window and user may select one of previously saved data files.
- ❖ *Printer Setup*
 - Opens the printer dialogue window to select and specify printer properties.
- ❖ *Select Printer Font*
 - Opens font dialogue to specify a font type and size for printing data and trajectory table.
- ❖ *Print*
 - Opens a printer selection window and prints selection.
- ❖ *What to print?*
 - Opens print selection window where user may specify what he wants to print


Print Selection Window



Picture 7: Print Selection

Here the user may specify what he wants to be printed. The main data is always printed and cannot be deselected. For normal printouts, we recommend to set the printer's sheet orientation to portrait.

- ❖ Set Language to
 - Select a language for the program windows. A sub menu opens showing the available languages.



Picture 8: Sub Menu Languages

- ❖ Exit Program
 - Close QuickTARGET Unlimited's windows. Terminate program. Also invoked by key ALT-F4.
- ❖ 0, 1, 2, 3.....
 - The names of the previously save data for easy access to frequently used data. Up to nine entries are displayed.


Menu Auxiliary Calculations



Picture 9: Menu Auxiliary Calculations

This menu provides useful calculations not provided by normal trajectory calculations.

- ❖ **Calculate Maximum Vertical Range**
 - The program tries to calculate the maximum altitude the projectile reaches by firing vertical into the air. While the results for ascending path represent the optimum what is possible (no significant yaw assumed, drag and BC's correct), the falling data are necessarily not very exact for spinning projectiles, because it will fall in most cases with base forward. "Base forward" drag characteristics are unknown and only a rough estimate of using double drag for falling part is used.
- ❖ **Calculate Maximum Horizontal Range**
 - The program calculates the maximum horizontal range in muzzle plane. Program assumes no yaw and results represent maximum possible distance, so far, drag data and BC's are correct.
- ❖ **Calculate Point Blank Range**
 - A window opens to specify the vertex of trajectory above (and below) Line Of Sight, sometimes named vital height. Program calculates zero-range to obtain desired point-blank-range. Results can be automatically transferred to *Sight-In* window.



Picture 10: Maximum Point-Blank-Range

❖ **Conversion of BC to Drag Model**

- Opens a window to calculate new BC valid for other drag model.

The screenshot shows the 'QuickTarget Unlimited > BC Conversion' dialog box. It is divided into two main sections: 'from BC 1:' and 'to BC 2:'. In the 'from BC 1:' section, a dropdown menu is set to 'G1-SAAMI Standard model', with 'BC 1' set to '.500' and 'Cd 1' set to '0.519'. In the 'to BC 2:' section, a dropdown menu is set to 'G5-Short 7.5° Boattail-6.19 cal tangent ogive'. Below this is a 'new BC's Atmosphere' section with a dropdown set to 'Standard ICAO' and four input fields: 'Barometric Pressure' (1013.246 mBar), 'Relative Humidity' (0 %), 'Temperature' (15.0 °C), and 'Altitude' (0 m). At the bottom of the 'to BC 2:' section, 'BC 2' is set to '.304' and 'Cd 2' is set to '0.316'. A 'Velocity' input field is set to '915 m/sec'. At the very bottom are 'Exit' and 'Calculate' buttons.

Picture 11: Convert BC to other Drag Model

- FRAME from BC 1
 - Select drag model for existing BC
 - Next to BC 1, enter a BC using specified drag model
 - Drag coefficient Cd1 is shown after selecting velocity
- FRAME to BC 2
 - Select new drag model
 - Select Atmospheric Conditions
 - Select Velocity
- Press Calculate
 - BC2 will display new BC, Cd2 will display new drag coefficient
- Exit
 - Button closes window

❖ **Calculate BC from two velocities and distance**

- Use two velocities at two different distances to calculate a BC. Drag model and Atmosphere from window Sight-In is used

QuickTarget Unlimited > BC Calculation

First Velocity 2785 ft/sec

Second Velocity 2560 ft/sec

Distance 100 yd

Atmosphere and Drag Model from Sight-In Form is used.

Exit Calculate

BC .4017

Picture 12: Calculate BC from 2 Velocities

Enter both velocities and distance, press Calculate button. BC is calculated. There is no need to care for lower and higher velocity entry window. Press Exit to close window.

❖ **Calculate Muzzle Velocity from Chronotach Velocity**

- Enter chronotach velocity and distance to screens center
- Press *Calculate* to calculate muzzle velocity. Drag, BC and Atmosphere settings from window Sight-In are used. User may select *Reassign* box to transfer velocity to Sight-In window.
- Press *Exit* to close window

QuickTarget Unlimited > Muzzle Velocity

Chronotached Velocity 2455 ft/sec

Distance from Muzzle to Screens 110 yd

Atmosphere, BC and Drag Model from Sight-In Form is used.

☐ Re-Assign calculated Velocity to Sight-In form

Exit Calculate

Projectile Velocity at Muzzle Exit 3161 ft/sec

Picture 13: Muzzle Velocity from Chronotach Velocity

❖ **Calculate Target Position**

- Using the settings of gun position (Latitude, Longitude, firing direction and Sight-In range from Sight-In window calculation returns Latitude and Longitude of target.

QuickTarget Unlimited > Target Position


Latitude of Target= 43 deg, 23 min, 31.6043 sec

Longitude of Target= 10 deg, 59 min, 47.0492 sec

Data input:
 WGS-84 Geoid (Vincenty algo.)
 Latitude of Gunsite (South=negative)
 Longitude of Gunsite
 Direction of Firing (Compass deg)
 Sight-In (Zero) Range

OK

Menu Options



Picture 14: Menu Options

- ❖ **Tooltip help enabled**
 - Enables or disables the pop-up window displaying help to each entry field
- ❖ **System sound on**
 - Enables or disables warning beep. No sound is played.
- ❖ **Coriolis Effect on**
 - User may switch on/off Coriolis effect within calculations caused by rotation of Earth. In reality, it is not possible to switch it off.
- ❖ **Edit Projectile**
 - Edit Projectile window opens. Because *QuickTARGET Unlimited* uses 6 BC's, projectile files should be edited using this window instead of *QuickLOAD's* or *QuickTARGET's* windows. While *QuickLOAD/QuickTARGET* work with the newer data, they will remove new BC information from the files. *QuickTARGET Unlimited* can use older files too.

Picture 15: Edit Projectile Window

This window serves to alter projectile data or to add projectile data.

❖ **FRAME Projectile Data**

- Drop-Down Box containing all projectiles of actual loaded file. Press triangular down-arrow on right side of field to open selection list.
- You may manually enter appropriate BC's into BC-fields and corresponding boundary velocities.

❖ **Drag Model to be used**

- Drop-Down box with available fixed drag models to which the entered BC's relate.
- Projectile weight
 - Enter mass of projectile
- Projectile Reference Diameter
 - Enter projectile diameter for small arms bullets, caliber (bore) diameter for projectiles with rotating bands.

❖ **Additional Properties**

- Projectile length
- Boattail Length/Hollowbase depth
- Boattail/Hollowbase large diameter
 - For Boattail diameter at shank-to-boattail transition, for hollowbase large diameter at base of projectile.
- Boattail/Hollowbase small diameter
 - For boattail the diameter at projectile's base, for hollowbase diameter at bottom of hollowbase inside projectile.
- Base Taper Angle full/half, output only
- Shot Start Pressure
 - Shot start pressure for use with QuickLOAD program
- Option Buttons
 - Boattail
 - HollowBase
 - FlatBase
 - Set according to shape of projectile

❖ **Buttons**


- Cancel
 - close window without making changes
- Delete
 - Select a projectile in the drop-down box and press Delete to delete data set also from file
- Save
 - Save entered data to projectile file.

❖ **Setup Screen Font**

- Windows font can be changed using this menu point. A font selection window opens to let you select to your own choice. Using too large font causes readability problems because text will be truncated or cut off.

❖ **Conversion Of Units**

- A small window opens containing a cross-calculator for most frequently used units.




Picture 16: Conversion of Units

This window provides bi-directional unit conversion. It makes no difference what field or what value is entered.

❖ **Maximum Projectile Drop below Sea Level**

- Opens small input window. User specifies Y-ordinate below sea level where calculation is stopped. Valid range is from -1 meter to -10000 meters. Recommended e.g. to display shotgun pellet trajectories, which drop steeply beyond 200 yards. If the ordinate limit is too large, the unimportant part of trajectory plot governs the graphic window, which might be undesirable.




Picture 17: Ordinate limit set to -1m (left) and -100m (right)

User's Settings of Units

The program uses user's settings of units unlike *QuickLOAD* and *QuickTARGET*.

The units are always displayed in a field right of the value field. A right mouse button click on this unit-field pops up a unit menu. (This menu is also activated while cursor is in value field by pressing CTRL-ARROW DOWN key combination)




Picture 18: Setting of Units

Example: pop-up unit window for length-units in field *Height of Sight above/below bore centerline*.

User may select the appropriate unit by clicking with left mouse button on desired unit or use key: Arrow-Up or Arrow-Down and press Enter key.

There are some exceptions:


1. The **MOA** units are not selectable
2. The **angle's** units are deg, rad and mils. When set to "deg", the user may enter decimal degrees, and by double-clicking into the value field (or press CTRL-W key) a small window opens allowing entering degrees, minutes and seconds. Note: because entries are additive, you must apply to each field a minus sign for negative angles.



Picture 19: Deg, Min, and Sec

3. When selecting **Wind speed** and Angle of **Wind** user may select unit of angle and unit of velocity as stated above, but by double-clicking into the value field (or press CTRL-W key) a wind-rose field opens to enter both direction and wind speed graphically.

Wind-Rose Window



Picture 20: Windrose Window

The windrose window enables the user to indicate wind direction and strength graphically.

The projectile in the picture points in shooting direction.

The direction of North to firing direction is shown by a yellow line and the word NORTH, as specified under **"Environmental Properties"** for the gunsite position **and** firing direction in Sight-In or in Table Setup window.

Wind is represented by a light blue *Wind-barb*, in this picture the direction is 49,5 deg from firing direction (a headwind and crosswind component is calculated) with a strength of 6,8 mph.

The user may left-click with mouse symbol over red point, hold button down and drag wind-barb to desired position. The position of red point relative to center of wind rose represents wind speed. The circles on the picture show wind speed values; here from 1 to 10 mph. User may drag red point outside of circles to obtain higher wind speeds.

The values in the upper left and upper right corners do not always show the actual wind data. They represent the mouse cursor position or the last mouse cursor position over the grid.

Using the keyboard to move wind-barb, they display actual data; so far, mouse cursor is outside of this window.

Keyboard commands are:

1. Arrow-Up to increase angle
2. Arrow-Down to decrease angle
3. Arrow-Right to increase speed
4. Arrow-Left to decrease speed
5. Enter Key or ALT-F4 to close window.

Gun Sight-In Conditions Window

Gun Dimensions

Line of Sight to Bore Centerline y	2	in
Line of Sight to Bore Centerline z	0	cm
Sight-In Gun Canting Angle	0	deg
Sight Adj. MOA per Click	0.344	MOA
Sight Adj. Definition Distance	91.44	m
Sight Adj. Displacement per Click	9.15	mm
Rifling Twist Length	10	in

Target Setup

☒ Zero-In Windage too

Sight-In (Zero) Range	300	m
Bullet Impact to Tgt. Center y	0	cm
Bullet Impact to Tgt. Center z	0	cm
Aiming Point to Tgt. Center y	0	cm
Aiming Point to Tgt. Center z	0	m

Gunsite Setup

Altitude of Gunsite	0	m
Gunsite Angle (up-downhill)	0	deg
Gun Muzzle Position GFX x	0	m
Gun Muzzle Position GFX y	0	m
Gun Muzzle Position GFX z	0	cm
Moving Gun Platform Vx	0	m/sec
Moving Gun Platform Vy	0	m/sec
Moving Gun Platform Vz	0	m/sec

Drag Model

G7

G7-Long 7.5° Boattail- 10 cal. tangent ogive

Sectional Density of Standard Projectile 1.000 lb./sq.in.

Projectile Properties

308, 155.5, Berger M T BT G7 #30416

BC_1	BC_2	BC_3	BC_4	BC_5	BC_6
0.237					

0 m/sec

Vel.1 Vel.2 Vel.3 Vel.4 Vel.5

Projectile Muzzle Velocity 2800 ft/s

Bullet Weight 155.5 gr

Environmental Properties

Direction of Firing (Compass deg)	0.0000000	deg
Latitude of Gunsite (South=negative)	45	deg
Longitude of Gunsite	10.0000000	deg

Wind Settings

Load from a File →

Wind Speed 0 mph

Wind Direction to Firing Direction 90 deg

Atmosphere Settings

Standard ICAO

Barometric Pressure	101324.6	Pa
Relative Humidity	0	%
Air Temperature	15.0	°C

Picture 21: Sight-IN Conditions window


Entry fields in this window from upper left to lower right:

❖ **FRAME Gun Dimensions:**

- Line of Sight to Bore Centerline y
 - Vertical distance between Line Of Sight and Centerline Of Bore. Gun not canted. **The selected units are initially used to format ordinates in trajectory graph.**
- Line of Sight to Bore Centerline z
 - Horizontal distance between Line Of Sight and Centerline Of Bore. Gun not canted. **The selected units are initially used to format ordinates in graph 'Topview'.**
- Sight-In Gun Canting Angle
 - Canting angle of gun while sighting in. Unusual for sight-in, but possible.
- Sight Adj. MOA per Click
 - Settings according to specifications of your guns sights, amount of angle per click or scale tick
- Sight Adj. Definition Distance
 - Settings according to specifications of your guns sights, reference distance at which correction value is obtained (normally 100 meters or 100 yards)
- Sight Adj. Displacement per Click
 - Settings according to specifications of your guns sights, amount of windage and elevation correction per scale tick or click
- Rifling Twist Length
 - Enter the twist length for one full turn of the bullet. Is used to calculate spin drift. Set to zero to avoid spin drift calculation. Use positive figures for Right Hand twist, negative for Left Hand twist.

❖ **FRAME Target Setup**

- Zero-In Windage too, Check Mark
 - When selected program corrects sideways displacement of impact caused wind and Coriolis effect. Only used when Sight-In range is specified
- Sight-In (Zero) Range
 - Distance from muzzle of gun to target when sighting-in. It is not necessary identical with zero-range because hold-on point and impact point on target have to be considered. **Setting Sight-In range to zero means no sight-in calculation takes place-this setting is used to calculate trajectories dependent on elevation angle (angle of departure)**
- Bullet Impact to Tgt. Center y
 - Vertical displacement between target center and point of impact
- Bullet Impact to Tgt. Center z
 - Horizontal displacement between target center and point of impact
- Aiming Point to Tgt. Center y
 - Vertical distance from Point of Hold to target center
- Aiming Point to Tgt. Center z
 - Horizontal distance from Point of Hold to target center



Picture 22: Target Data Definition

❖ **FRAME Gunsite Setup:**

- Altitude of Gunsite
 - Position of gunsite above or below sea level. Use at best GPS altitude data for altitude above or below Earth geoids surface. This is also the position of the origin of the Ground-Fixed-Frame of coordinates used by calculations. Value is also used to determine atmospheric data from Standard Atmospheres at this altitude. While trajectory calculation is in progress new altitude data for atmosphere and gravity is calculated by each integration step, dependent on projectile's trajectory altitude.
- Gunsite Angle (up-downhill)
 - Angle between horizontal plane and line from gun's muzzle to target's center, or in case of "**Sight-In range = 0**" angle between Centerline Of Bore and horizontal plane = approximately Angle Of Departure
- Gun Muzzle Position GFIX x
 - Horizontal position of gun muzzle before (= +) or behind (= -) Ground-Fixed-Frames y-z-plane, X-axis points into firing direction
- Gun Muzzle Position GFIX y
 - Vertical position of gun muzzle above (= +) or below (= -) Ground-Fixed-Frames x-z-plane, Y-axis points upward
- Gun Muzzle Position GFIX z
 - Sideways position of gun muzzle right (= +) or left (= -) Ground-Fixed-Frames x-y-plane, Z-axis points to the right

- Moving Gun Platform Vx
 - Gun is moving with velocity to be specified, component of velocity in x-direction
- Moving Gun Platform Vy
 - Gun is moving with velocity to be specified, component of velocity in y-direction
- Moving Gun Platform Vz
 - Gun is moving with velocity to be specified, component of velocity in z-direction


❖ **Drag Model:**

- User may select a drag model of his choice
 - Standard Drag Model is G1. Others like GS can be used for shotgun pellets together with a small shotgun pellet file available in the bullet section. Because the other models like G2, G5 etc. are based on different sectional densities than G1 (SD=1) they seem not to be useful,. The author hopes that those other models are corrected to SD=1, but has not found any evidence about that matter in literature.
 - The small rectangle in the upper right corner shows the abbreviated name of selected model.
 - The sectional density of the reference projectile is displayed below the selection box of drag model
 - User may load Non-Standard-Drag data:



Click here to open file
dialogue window to load a
different drag file


A standard windows file window is opened displaying some additional drag table files. (I apologize for the German window, but I have no English version installed on my computer, the English window should look similar, but with English text.)



Picture 23: Open Drag File Window


❖ **Projectile**

- User may select a projectile file of his choice
 - The dropdown menu contains all projectiles of loaded projectile- or bullet file
 - The small rectangle in the upper right corner shows the abbreviated name of selected projectile file




Click here to open file
dialogue window to load a
different projectile file

A standard Windows file window is opened displaying some additional bullet files.



Picture 24: Open Bullet File Window

- BC Fields:
 - Under *Projectile Selection box* there are 6 entry fields to specify up to 6 BC's and 5 velocities to each bullet. Fields have to be filled from left to right, the last right standing BC does not need a boundary velocity, it should be set to zero
- Projectile Muzzle Velocity
 - Enter projectile's muzzle exit velocity. By pressing button to load data from *QuickLOAD* the value is automatically overwritten.
- Bullet Weight
 - Enter mass of bullet. By pressing button to load data from *QuickLOAD* the value is automatically overwritten.
- ❖ **FRAME Environmental Properties**
 - Direction of Firing (Compass deg)
 - Enter direction of fire to North direction, from muzzle to target center. Angle taken from compass, between North and line to target, clockwise increasing. North= 0 deg, East = 90 deg, South =180 deg and West=270 deg.
 - Latitude of Gunsite (South=negative)
 - Latitude of Gun Position. Best use GPS data. Degrees range from 0 (Equator) to 90 deg = Pole, northern hemisphere positive values, southern hemisphere negative values. If unknown, 40 to 50 deg is useable value for average North America or Europe.
 - Longitude of Gunsite
 - Longitude of Gunsite position, values may range from 0 to 180 deg East of Greenwich meridian and 0 to -180 West of Greenwich meridian, or even 0 to 359,9999 deg East of Greenwich meridian.
- ❖ **FRAME Wind Settings**
 - Load from a file --> (or file name)
 - Button to open file open dialog window to read a wind profile file



Click here to open file dialogue window to load a wind-profile file

- Wind Speed
 - Enter the wind speed in desired units, double-click to field to open graphical input
- Wind Direction to Firing Direction
 - Enter an angle of direction relative to firing direction from headwind = $0^{\circ} \simeq$ 12 o'clock over crosswind from right = $90^{\circ} \simeq$ 3 o'clock over tailwind = $180^{\circ} \simeq$ 6 o'clock to crosswinds from left = $270^{\circ} \simeq$ 9 o'clock; double-click on field to open graphical input window.
- ❖ **FRAME Atmosphere Settings:**
 - Drop down selection box for different atmospheres; may select from 3 choices
 - Standard ICAO (up to 20 km identical to US Standard Atmo 1976)
 - Actual Standard Sea Level conditions. Entry fields for barometric pressure, relative humidity and temperature are disabled.
 - U.S. Army Standard Metro (obsolete)
 - Some BC's may be based on that data. Entry fields for barometric pressure, relative humidity and temperature are disabled.
 - Instrumental Readings
 - Actual local readings from instruments. Corrections for other altitudes are calculated by Std. ICAO formulas. Entry fields for barometric pressure, relative humidity and temperature are enabled.
 - Barometric Pressure
 - Value according to standard, but corrected for altitude; real value in case of Instrumental Readings
 - Relative Humidity
 - Value according to standard, but corrected for altitude; real value in case of Instrumental Readings
 - Air Temperature
 - Value according to standard, but corrected for altitude; real value in case of Instrumental Readings

Trajectory Table Conditions Window

Picture 25: Trajectory Table Conditions

Click here to set trajectory table conditions to sight-in conditions

In the previous window, all the data necessary to describe how the gun was sighted-in has been entered and collected. Now we must specify the conditions under which the user wants to shoot, e.g. conditions for the trajectory table and graphs. In most cases conditions will equal Sight-In conditions, if they differ one must set up Table conditions.

E.g., gun was sighted-in at Trout Run, PA and now there is a F-Class-Match in South Africa. How will my gun react at this Match?: Set Sight-In conditions to range and atmosphere data at the range in Denver and Table conditions to range- and atmosphere data in South Africa (so far known). Now calculate and look what corrections to windage and elevation are necessary.


Data fields of *Trajectory Table Conditions* Window from upper left corner to lower right corner:

- ❖ **Gun/Ammunition**
 - Description of gun and ammunition used. Will be printed on trajectory table.
- ❖ **Comment**
 - Add further comment to trajectory table. Will be printed on trajectory table.
- ❖ **FRAME Table Scale (must be filled-in even for Sight-In = Trajectory)**
 - Maximum Distance for Table
 - Enter the maximum range for table. Up to this value the calculation proceeds, so far the projectile can reach this range. Otherwise calculation is stopped when projectile falls below sea level, specified in QTM_.set file under section [startup] negativeY = -20 (means -20 meters stop level)
 - Range Increment
 - Trajectory table distance step width. For each multiple of this value a line of data is printed. This field's unit is initially used to define the range units.

- If Range Increment is set too coarse, the trajectory graphs will look somewhat angular. Use different settings when you want to have a smooth graph or a short table.
- Table Energy Units
 - Select the energy units you like to have printed in trajectory table.
- ❖ **FRAME Gunsite Data**
 - Altitude of Gunsite
 - Enter the altitude of gunsite for which the table will be calculated
 - Gunsite Angle (uphill/downhill)
 - Enter the angle between muzzle level plane and line from muzzle to target center
 - Gun Muzzle Position GFIX x
 - Horizontal position of gun muzzle before (= +) or behind (= -) Ground-Fixed-Frames y-z-plane, X-axis points into firing direction
 - Gun Muzzle Position GFIX y
 - Vertical position of gun muzzle above (= +) or below (= -) Ground-Fixed-Frames x-z-plane, Y-axis points upward
 - Gun Muzzle Position GFIX z
 - Sideways position of gun muzzle right (= +) or left (= -) Ground-Fixed-Frames x-y-plane, Z-axis points to the right
- ❖ **FRAME Table Environment**
 - Direction of Firing (Compass deg)
 - Enter direction of fire to North direction, from muzzle to target center. Angle taken from compass, between North and line to target, clockwise increasing. North= 0 deg, East = 90 deg, South =180 deg and West=270 deg.
 - Latitude of Gunsite (South=negative)
 - Latitude of Gun Position. Best use GPS data. Degrees range from 0 (Equator) to 90 deg = Pole, northern hemisphere positive values, southern hemisphere negative values. If unknown, 40 to 50 deg is useable value for average North America or Europe.
 - Longitude of Gunsite
 - Longitude of Gunsite position, values may range from 0 to 180 deg East of Greenwich meridian and 0 to -180 West of Greenwich meridian, or even 0 to 359,9999 deg East of Greenwich meridian.
- ❖ **FRAME Table Atmosphere Settings**
 - Drop down selection box for different atmospheres; may select from 3 choices
 - Standard ICAO (up to 20 km identical to US Standard Atmo 1976)
 - Actual Standard Sea Level conditions. Entry fields for barometric pressure, relative humidity and temperature are disabled.
 - U.S. Army Standard Metro (obsolete)
 - Some BC's may be based on that data. Entry fields for barometric pressure, relative humidity and temperature are disabled.
 - Instrumental Readings
 - Actual local readings from instruments. Corrections for other altitudes are calculated by Std. ICAO formulas. Entry fields for barometric pressure, relative humidity and temperature are enabled.
 - Barometric Pressure
 - Value according to standard, but corrected for altitude; real value in case of Instrumental Readings
 - Relative Humidity
 - Value according to standard, but corrected for altitude; real value in case of Instrumental Readings
 - Air Temperature
 - Value according to standard, but corrected for altitude; real value in case of Instrumental Readings

❖ **FRAME Table Wind**

- Load from a file --> (or file name)
 - Button to open file open dialog window to read a wind profile file



Click here to open file
dialogue window to load a
wind-profile file

- Wind Speed
 - Enter the wind speed in desired units, double-click to field to open graphical input
- Wind Direction to Firing Direction
 - Enter an angle of direction relative to firing direction from headwind = $0^\circ \simeq$ 12 o'clock over crosswind from right = $90^\circ \simeq$ 3 o'clock over tailwind = $180^\circ \simeq$ 6 o'clock to crosswinds from left = $270^\circ \simeq$ 9 o'clock; double-click on field to open graphical input window.
- Table Gun Canting Angle
 - Canting angle of gun for table. Unusual, but possible.

❖ **Button Use-Sight-In Data for Table**

- Retrieves data from *Sight-In* window and puts it into equivalent fields in *Table* window

NOTE: Unusual wind conditions may result in incomplete trajectory data output. The output has stopped either when calculated array of data becomes too large to be displayed or the output window signals an overflow by very long ranges and small range increments. In such a case, it is possible to use all data by transferring data to Excel. The only drawback is that data to Excel is raw format that means all data are in SI units like meters, meters/second and many decimals behind the decimal point. However, it is likewise easy to change in Excel everything you want.

Displaying Results




When *Output window Table* or *window Diagram* is positioned in foreground the main menu appearance changes to the above shown items. To return to standard Main Menu select Main Menu from this menu. This menu bar is created while displaying trajectory table. When displaying trajectory graphs, the following menu bar is shown:



Main Menu returns control to main window.

Menu Copy to...



Picture 26: SubMenu Copy to...

The sub menu *Copy to...* contains the following selections


- ❖ *Clipboard*;
 - Copies the contents of output window to clipboard; you may use the Insert or Paste function of text- or graphics programs to paste it into foreign program.
- ❖ *Print Image*;
 - Sends a bitmap (pixel) image of window to the default printer.
- ❖ *File*;
 - Opens File save... dialog; you may save window contents as bitmap- or as text file.
- ❖ *Excel*;
 - When Microsoft® Excel® (part of MS-Office) is installed on your computer, Excel opens and the table is transferred to Excel's spreadsheet via 'Object automation'. Object automation must be properly installed for Excel (which is done by installation of MS-Office installer).

Menu Output Options...




Picture 27: Output Menu Options...

- ❖ **Save Trace**
 - Stores temporarily the results of calculation (Trajectory table) in a collection of results.
- ❖ **Delete Traces;**
 - Deletes all temporarily stored calculations.
- ❖ **Grid;**
 - Axis' grid on / off
- ❖ **Hatched Vital Zone;**
 - Display zone defined in input window under "Vital height to LOS..." as gray-hatched area on graph.
- ❖ **Marks On**
 - Displays Vertex, Point-Blank or Zero-Range marks in graphs
- ❖ **Line Thick**
 - Toggles between two different line types in graph
- ❖ **Axis, displays a sub menu:**



- ❖ **Color settings;**
 - Alter axis' colors. Colors selected will also be used for printing on color printers. (Sometimes colors visible on screen do not work with printers!)
- ❖ **Font**
 - Select new font for graph. Trajectory Table Font is selected via Main menu *Font* which is shown instead of *Options...* menu

Menu Show...



Picture 28: Menu Show...

In this menu user decides what he wants to view:

Trajectory Table

QuickTarget Unlimited> Table

Sight-IN Data	: Standard ICAO	Barometric Pressure	: 101324.6 Pa
Altitude	: 0.0 m	Temperature	: 15 °C
Humidity	: 0 %	Angle of Site	: 0.0 deg
Latitude of Site	: 50.0344 deg	Longitude of Site	: -8.5714 deg
Direction to Target	: 45.0 deg	Canting of Gun	: 0.0 deg
Wind Speed	: 0.0 km/h	Direction of Wind	: 0.0 deg

Bullet : .224, 77, Sierra HPBT MatchK 9377
 Bullet Weight : 4.99 g
 Muzzle Velocity : 850.0 m/s
 Twist Length : 10.0 in , Right Hand Twist
 Gyroscop. Stability : 1.15
 Ballistic Coefficients
 BC1 = 0.372, @V > 914 m/s
 BC2 = 0.362, @V > 762 m/s
 BC3 = 0.362, @V > 518 m/s
 BC4 = 0.343, @V > 0 m/s

Drag Model used : G1
 Sectional Density of Standard Projectile : 1 lb./sq.in.
 File: G1-SAAMI Standard model

Users's comment :

Sight-In Clicks: 1 Click = 0.66 cm @ 100.0 yd
 Height of Sight Above Bore Axis : 8.0 cm
 Gun is Sighted-In at 100 m by sighting-in at level firing
 Angle betw. LOS and LOD (above Angle of Site= 0 deg.) = 0.0416992 deg.

Range	Velo	Time	Energy	Path	Path	Correction to	Correction to	Total		
	city	of		LOS	LOS	Elevation for	Windage for	Drop		
		Flight		Y	Z	Zeroing	Zeroing			
m	m/s	sec	J	cm	cm	Click	MOA	Click	MOA	cm
0	850	0,0000	1803	-8,0	0,0	-----	-----	-----	-----	0,0
25	828	0,0298	1713	-4,6	0,0	+25,4	+6,34	+0,2	+0,04	0,4
50	807	0,0604	1626	-2,1	0,0	+5,8	+1,46	+0,1	+0,03	1,8
75	786	0,0917	1543	-0,6	0,0	+1,0	+0,26	+0,1	+0,01	4,0
S 100	766	0,1239	1464	0,0	0,0	0,0	0,00	0,0	0,00	7,3
M 101	765	0,1252	1461	0,0	0,0	0,0	0,00	0,0	0,00	7,4
X 102	764	0,1266	1458	0,0	0,0	0,0	0,00	0,0	0,00	7,6
125	746	0,1570	1388	-0,5	0,0	+0,5	+0,13	-0,1	-0,01	11,6
150	726	0,1910	1315	-2,1	0,1	+1,9	+0,47	-0,1	-0,03	17,0
175	706	0,2259	1244	-4,8	0,2	+3,8	+0,95	-0,2	-0,04	23,6
200	687	0,2618	1177	-8,8	0,3	+6,0	+1,51	-0,2	-0,05	31,3
225	668	0,2987	1113	-14,1	0,5	+8,6	+2,15	-0,3	-0,07	40,4
250	649	0,3367	1051	-20,7	0,6	+11,4	+2,85	-0,3	-0,08	50,9
275	631	0,3758	993	-28,8	0,8	+14,4	+3,60	-0,4	-0,10	62,8
300	613	0,4160	936	-38,5	1,0	+17,6	+4,41	-0,5	-0,12	76,3


Picture 29: Trajectory Table Window

The trajectory table shows **range units** according to **Range Increment** unit settings, **energy** to **Energy** units and **path units** according to **Line of Sight to Bore Centerline** units as defined in **Table Setup** and **Sight-In** window. Lines containing Sight-In range (S), Max height above Line of Sight (M) and Zero-Range (bullet path crossing LOS=X) are marked with the corresponding characters in the first column. **Sight-In range may differ from Zero-Range because of non-zero impact settings and/or different condition between sight-in data and trajectory table conditions.**

Changing Graph's Appearance


Some additional functions are provided to shorten settings of graph without using menu:

Graph Window



Picture 30: Graph showing mouse coordinates


Similar to *QuickLOAD*, moving the mouse cursor's crosshair over the graph's area displays readouts of position of cursor in values and units displayed in graph.



Picture 31: Changing Graph Axis' Units


Left-Clicking into the above yellow marked region (area about width and height of scale numbers), a pop-up menu opens, allowing you to select a unit for the corresponding axis, as you prefer. Units selected here are also used for printing. The selected units are valid for each

type of graph separately. Time units (seconds) are not changeable. After restart of the program default units according to settings in Sight-In and Table window are used.




Picture 32: Selecting the Type of Graph

By right clicking (right button of mouse) over the grid area the menu to select a graph type is opened.




Picture 33: Selecting Graph Options

By right clicking outside of grid, the graph options menu pops-up.



Picture 34: Edit Line of Legend

While mouse cursor is over a legend line and left clicking, a small window opens allowing you to change the displayed text. Text is also printed on printer output. It can also be invoked by pressing the corresponding number Key (0-9)




Picture 35: Delete Legend Line and Single Trace

While mouse cursor is over a legend line and clicking right, the program assumes that you will delete the corresponding trace. If only one trace is displayed, this function is disabled.


Examples of Different Graphs in the Order of Menu

Drag Table Graph




Picture 36: Drag Table graph, here G1- C_d -graph

This window shows the actually used drag table, either G-table or C_d -table or K_d -table.



Picture 37: G1 - K_d Graph

K_d is old-fashioned ballistics drag representation. $K_d = \frac{\pi}{8} \times C_d$




Picture 38: G1 -Function

The G-function starts for $m=0$ at zero. It is a function containing aside of C_d the standard air density, standard speed of sound and the term $\frac{\pi}{8 * 144}$. While C_d and K_d are dimensionless factors, G is not.

QuickTARGET Unlimited can use all three types of drag coefficients. The file format of external drag coefficient files is explained in Appendix.


Drop in Ground-Fixed-Frame



Picture 39: Graph of Total Drop in Ground-Fixed-Frame

Total drop from line of departure vs. range


Path in Ground-Fixed-Frame



Picture 40: Trajectory Path in Ground-Fixed-Frame

Path with respect to gunsite level plane


Path versus Line Of Sight



Picture 41: Trajectory Path vs. Line of Sight

The range-axis is the LOS (Line Of Sight). The maximum point-blank-range has been calculated, before calculating range data. Therefore, it is possible to mark the vital zone by gray-hatched area.


Velocity Graph



Picture 42: Velocity Graph

Velocity graph of a long-range trajectory. Velocity drops up to 1900 yards by reaching the trajectory vertex and then gains some velocity by falling to the end of range.


Energy Graph



Picture 43: Energy Graph

This energy graph belongs to the velocity graph shown above


Time of Flight



Picture 44: Time of Flight Graph

In time of flight, graph user may only change scale of range, but not time.


MOA Elevation Correction to Zero-In



Picture 45: MOA Elevation Correction Graph

Zero range is 2700 yards. At this range is no correction necessary, but to set zero for shorter ranges, it is necessary to adjust the amount of MOA according to new zero-range.


MOA Azimuth Correction to Zero-In



Picture 46: MOA Azimuth Correction Graph

To adjust azimuth or windage for new zero-range applies the settings shown in graph. Note that at shorter ranges, a positive correction to the right is necessary and for ranges above 1400 yards, a negative correction to the left is necessary due to either Coriolis effect or wind influence.


Top View: Azimuth Deflection




Picture 47: Top View of Path

Top view of trajectory showing zeroed-in windage. Deviation is up to zero-range slightly to the left, after zero to the right of Line Of Sight.


Different Examples of Graphs




Picture 48: Trajectories for different zero-ranges



Picture 49: Graph with different angles of departure for shotgun pellets No.7 1/2




Picture 50: Top view of shotgun pellet's trajectory



Picture 51: Trajectory in x-y plane under extreme wind conditions

Absolute crazy head-, tail-, up- and downwind conditions can create such an unusual trajectory. Nevertheless, zero-range match is found at 100 yards. Those winds will blow the shooter away.



Picture 52: Top-view of extreme crosswind influence

Extreme crosswind causes extreme azimuth or windage deflection, but program corrects to obtain zero range at 1000 yards.

APPENDIX

Drag Table Files

Drag table files readable to the program must follow some rules. First, it should be plain ASCII text files.

```
CMF , G1_McCoyBook
0      0.267719059
0.5    0.206642467
0.6    0.206642467
0.7    0.220893672
0.8    0.259575513
0.9    0.348136571
0.95   0.415320821
1      0.489630674
1.05   0.552743152
1.1    0.598550595
1.2    0.650465698
1.3    0.670824561
1.4    0.674896334
1.5    0.668788675
1.6    0.658609243
1.8    0.63214272
2      0.603640311
2.2    0.579209674
2.5    0.549689322
3      0.522204856
3.5    0.513043367
4      0.509989538
```

On the left side, there is the content of the file

G1_McCoyBook.drg

The first line contains data and information. Any empty line causes an error when reading the file. Entries in the first line have to be separated by a comma. The first left entry tells the program what is in the file: If the first character is a

- **C** the program assumes Cd values
- **K** the program assumes Kd values
- **G** the program assumes G function values.

The following two characters **MF** or **FM** tells the program the sort order of data, MF means first Mach number and then value, FM means first column contains value followed by Mach number column.

The file contains two data columns. In the case shown the left column are the mach numbers and the right one the corresponding C_d values. Both data had to be separated by either a space or a comma or both. The decimal point has to be a point and no comma.

Because the reference projectile mass is 1 lb and the diameter is 1 inch, the sectional density is also 1. No further data is needed.

Picture 53: G1 C_d file

```
CFM, M-80, .009446, .00782, .028143, BRL-MR-1833 Piddington
0.13 0
0.13 0.189
0.129 0.594
0.137 0.77
0.18 0.9
0.314 0.972
0.45 1.001
0.458 1.06
0.43 1.295
0.42 1.378
0.386 1.615
0.356 1.867
0.346 1.943
0.296 2.445
0.283 2.769
0.278 4
0.278 5
```

Left there is the contents of file

308-M80-BRL.drg

This is the standard .30 cal NATO projectile and because it has not 1lb mass and 1 inch diameter, additional specs are needed:

CFM is like above G1 specified, M-80 is projectile's name, 0.009446 is the mass in kg, .00782 the diameter in meters, .028143 is the length in meters and BRL-MR-1833 Piddington is the source of data.


Picture 54:

Specific Drag File for one Projectile

The first line contains order type, name, mass in kg, diameter in meters, length in meters, source as comment. Commas must separate all 6 entries. The length of the file is not restricted.

Wind Profile Files

Wind profiles may also be specified in a file. In case of shooting over a canyon, or when forest or a ridge covers half of the range spans along the range wind cannot be defined by a single wind speed and direction. The scheme for managing wind profiles is shown below:



Picture 55: Scheme of Windlayers

Extension of windlayer file is .wif . All text must be plain ASCII code.

First line serves as comment. Second line has to be the first line containing data. Consecutive lines must not contain empty lines. A data line contains five numerical values, separated by space or a comma character. The decimal point is a dot and not a comma!

All data are in meters or meters per second units, data are separated in layers and zones. The first zone of wind stretches from Range 1= 0(meters) to Range 2 (in direction of firing or GFX X-axis)

- The second zone stretches from Range 2 to Range 3
- The third zone stretches from Range 3 to Range 4
- The fourth zone stretches from Range 4 to Range 5
- The fifth zone reaches from Range 5 to infinite

Following sample contains one layer, which goes from alti1 (i.e. -1500 meters) to infinite altitude User may define as many zones as he needs (<30000), each layer must contain same number of zones, and zones may have different boundary ranges in different layers

Example of one 5-zone layer:

windspeeds			from Range	from lower altitude
vx1	, vy1	, vz1	, Range1_1	, alti1
vx2	, vy2	, vz2	, Range2_1	, alti1
vx3	, vy3	, vz3	, Range3_1	, alti1
vx4	, vy4	, vz4	, Range4_1	, alti1
vx5	, vy5	, vz5	, Range5_1	, alti1

User may add additional layers (maximum not tested):

Now the first layer is valid to altitude 2 and second up to infinite.

- Second Layer:

```
vx1      , vy1      , vz1      , Range1_2      , alti2
vx2      , vy2      , vz2      , Range2_2      , alti2
vx3      , vy3      , vz3      , Range3_2      , alti2
vx4      , vy4      , vz4      , Range4_2      , alti2
vx5      , vy5      , vz5      , Range5_2      , alti2
```

and so on...

windprofile4

```
0 , +50 , +5 , 0 , -500
0 , -50 , -5 , 200 , -500
0 , -50 , -5 , 400 , -500
0 , +50 , +5 , 600 , -500
0 , 0 , +5 , 800 , -500
```

This is the content of file **testwindyayer.wif**
This causes such crazy trajectories displayed here in the manual as examples. Valid from altitude - 500 meters to infinite altitude, range 5 from 800 meters to infinite distance.

Picture 56: Contents of a wind profile file

Bibliography

Books and reports mentioned here contain useful information on Exterior Ballistics calculations. We recommend also reading all available manuals and brochures of bullet manufacturers to collect information about their bullets.

- | | |
|---------------------------|---|
| McShane; Kelley; Reno | <i>Exterior Ballistics</i> , The University of Denver Press, 1953 |
| Molitz, Strobel | <i>Äußere Ballistik</i> , Springer-Verlag Berlin, 1963 |
| Lieske R.F., Reiter M.L. | <i>Equations of Motion for a Modified Point Mass Trajectory</i> , BRL-TR-1314, MD, March 1966 |
| Duncan L.D., Engebos B.F. | <i>A Six-Degree-of-Freedom Digital Computer Program for Trajectory Simulation</i> , Atmospheric Sciences Lab, White Sands Missile Range, NM, 1967, AD664116 |
| Hauck, Günter | <i>Äußere Ballistik</i> , Militärverlag der DDR, 1.Aufl. 1972 |
| HMSO | <i>Textbook on Ballistics and Gunnery</i> , Volume One, Part I & II, London 1987 |
| Bradley, J.W. | <i>An Alternative Form of the Modified-Point-Mass Equation of Motion</i> , BRL-MR-3875, MD, 1990 |
| Lieske R.F. | <i>Use of the Magnus Force in the Modified-Point-Mass Trajectory Model</i> , BRL-MR-3870, Md, 1990 |
| Lieske R.F, Danberg J.E. | <i>Modified-Point-Mass Trajectory Simulation for Base-Bleed Projectiles</i> , BRL-TR-3321, MD, 1992 |
| Farrar; Leeming | <i>Military Ballistics. A Basic Manual</i> , Brassey's Publishers Ltd., Oxford 1995 |
| NATO Stanag 4355 | <i>The Modified Point-Mass-Trajectory Model</i> , 2nd Edition, AC/225-D/1319, 1997 |
| McCoy, Robert L. | <i>Modern Exterior Ballistics</i> , Schiffer Publishing Ltd., Atglen, PA, 1999 |
| Litz, Bryan | <i>Applied Ballistics for Long Range Shooting</i> , Applied Ballistics LLC, Cedar Springs, MI, 2009 |

List of Illustrations

Picture 1: Start and Disclaimer window	6
Picture 2: Ground-Fixed Frame of Coordinates	7
Picture 3: Gunsite Angle	7
Picture 4: Main Window	8
Picture 5: Main Menu Bar	9
Picture 6: File Menu	9
Picture 7: Print Selection	10
Picture 8: Sub Menu Languages	10
Picture 9: Menu Auxiliary Calculations	11
Picture 10: Maximum Point-Blank-Range	11
Picture 11: Convert BC to other Drag Model	12
Picture 12: Calculate BC from 2 Velocities	13
Picture 13: Muzzle Velocity from Chronotach Velocity	13
Picture 14: Menu Options	14
Picture 15: Edit Projectile Window	14
Picture 16: Conversion of Units	15
Picture 17: Ordinate limit set to -1m (left) and -100m (right)	16
Picture 18: Setting of Units	17
Picture 19: Deg, Min, and Sec	17
Picture 20: Windrose Window	18
Picture 21: Sight-IN Conditions window	19
Picture 22: Target Data Definition	20
Picture 23: Open Drag File Window	21
Picture 24: Open Bullet File Window	22
Picture 25: Trajectory Table Conditions	24
Picture 26: SubMenu Copy to	27
Picture 27: Output Menu Options	28
Picture 28: Menu Show	28
Picture 29: Trajectory Table Window	29
Picture 30: Graph showing mouse coordinates	30
Picture 31: Changing Graph Axis' Units	30
Picture 32: Selecting the Type of Graph	31
Picture 33: Selecting Graph Options	31
Picture 34: Edit Line of Legend	32
Picture 35: Delete Legend Line and Single Trace	32
Picture 36: Drag Table graph, here G1-C _d -graph	33
Picture 37: G1 - K _d Graph	33
Picture 38: G1 -Function	34
Picture 39: Graph of Total Drop in Ground-Fixed-Frame	34
Picture 40: Trajectory Path in Ground-Fixed-Frame	35
Picture 41: Trajectory Path vs. Line of Sight	35
Picture 42: Velocity Graph	36
Picture 43: Energy Graph	36
Picture 44: Time of Flight Graph	37
Picture 45: MOA Elevation Correction Graph	37
Picture 46: MOA Azimuth Correction Graph	38
Picture 47: Top View of Path	38
Picture 48: Trajectories for different zero-ranges	39
Picture 49: Graph with different angles of departure for shotgun pellets No.7 1/2	39
Picture 50: Top view of shotgun pellet's trajectory	40
Picture 51: Trajectory in x-y plane under extreme wind conditions	40
Picture 52: Top-view of extreme crosswind influence	41
Picture 53: G1 C _d file	42
Picture 54: Specific Drag File for one Projectile	42
Picture 55: Scheme of Windlayers	43
Picture 56: Contents of a wind profile file	44